

UMODA05 TBOLC 500-500-17 MWOBC 882X1B06

References

- FM 3-35.4, Deployment Fort-to-Port, Appendix I
- FM 4-01.011, Unit Movement Operations, Appendix D,
- FM 55-30, Army Motor Transport Units and Operations, Chapter 10
- FORSCOM/ARNG Reg 55-1, Unit Movement Planning,
 Chapter 5
- TB 55-46-1, Standard Characteristics for Transportability of Military Vehicles and Outsized/Overweight Equipment

Movements

• TEA PAM 55-20, Tiedown Handbook for Truck

Scope of Lesson

- Load Plan Cycle
 - Planning the Load
 - Testing the Load
 - Inspecting the Lo
 - Documenting the Load





- Load distribution
- Not containerized
- Not weatherproofed
- Not secured











- Not secured
- May cause injury to personnel
- May cause damage to windshield

Planning the Load

Planning the Load

- Planning for packing & loading unit equipment is an important deployment preparation activity
 - Involves identifying actual space, weight, packaging material & external transport requirements
 - Proper planning saves valuable time when ordered to deploy

Cube

- To determine how much space is needed, planners must first determine how much cargo needs to be moved
- The primary factor is cubic feet of space required for cargo shipments

Cube (Cont)

- Determine Volume in cubic feet
 - Step 1: Take measurements of the length, width and height in inches
 - Step 3: Mwitiel the artswer by 1 72 beight get

volume in cubic feet (1728 inches in

a cubic foot)

Cube (Cont)

 A - Add cubic feet measurements of all cargo together to get the total cubic feet requirement

- requirement
 B Add cubic feet measurements of all cargo vehicles to get the total cubic feet of cargo carrying space available
- Subtract B from A to determine external cargo lift assets required, if any
- IT IS NEVER THAT SIMPLE!!!!!!!

Cube (Cont)

- We do add cubic foot measurements of all cargo to get total cubic foot requirement
- Not all equipment comes in a rectangular shaped box
- Odd sized and heavy items require other considerations
- Maximize use of available space
- Usually will cube out before weigh out

Weight

- Weight of most military cargo is marked on the package. Unmarked cargo must be weighed before loading
- Total shipment weight should equal the sum of the individual cargo weights
- Weigh loaded vehicle and record on AUEL
- Dense cargo can cause a vehicle's weight limit to be reached before the cargo space is filled

Vehicle Data Plate

- Axle weight capacity information is located on the vehicle data plate
- 3 different loading weights:

Empty


Cross country

Highway vehicle weight

Maximum loaded vehicle weight should always be the cross country weight

Vehicle Data Plate (Cont)

 <u>Never</u> exceed weight capacity of vehicle indicated on vehicle data plate



Always use cross country weight limits


Material Handling Equipment

 Consider capabilities of available materiel handling equipment (MHE)
 Ensure MHE is staged along with required

Ensure MHE is staged along with required packing material prior to loading

 MHE capacity must be equal to or greater than t

 Determine external MHE requirements (consider destination)





Loading Considerations

 Consider likely deployment configuration for vehicles carrying secondary loads


 If deploying by rail, air or sea, then the secondary load cannot exceed reduction dimensions

 TB 55-46-1 provides base and reduced cargo body dimensions for vehicles


Testing the Load

STEP 6: Develop Vehicle Load Plans for Unit Equipment

- Don't exceed payload capacity
- Document planned loads for organic vehicles and trailers carrying secondary loads (FORSCOM 285-R or DA 5748-R)
- Vehicles may have to be reduced according to mode of transportation and type of move
- Consider vehicle modifications (approved by SDDC TEA) and reflected in AUEL/DEL or OEL/UDL
- Test planned loads (every year for AC, every two years for RC)







Balancing

Balancing weightsiderations
 Unbalanced loads cause
 damage

Rules of thumb on weight balance heavy cargo on the bottom balance Distribute heavy items evenly over vehicle bed
 Check vehicle data plate for maximum axle weights

Ref: FM 55-30, Para 10-5b

Checked for maximum axle weight?



Load Considerations


- Pack cargo so it doesn't shift (use B & B)
- Keep load as low as possible in vehicle
- Consider multi-stops when loading
- Load items of uniform size and shape (where possible) for easier tie-down
- Use boxes and containers to move smaller items

LOAD SMART!!! LOAD SAFE!

Testing the Load - Loading Vehicles -

Select the right vehicle for the right job





Wrong

Right

Ref: FM 55-30, Para 10-5a


Well balanced load? Right Vehicle for the Right Job



Load Placement in Trucks & Semitrailers


• Tires, axles & frame are designed to carry a load distributed as shown





Load Placement in Trucks & Semitrailers

• Distribute trailer Cont qually between the rear tires & the fifth wheel to ensure load transfers to the tractor



Load Placement in Trucks & Semitrailers (Cont)



Load can bend the frame, overload front tires and make steering harder



Place fieavy part of load near rear axle for proper tire loading and to keep frame from bending

Load Placement in Trucks & Semitrailers (Cont)

Set a Right entrated load just ahead of the rear axle with the longest side on

the floor

Wrong
Load can bend the frame, overload rear tires and make steering almost impossible

Load Placement in Trucks & Semitrailers (Cont)

WRONG

This plant overloads one spring and set of tires, brakes could lock on the

light side causing skids 36

שוון שוון 🕽 🎍 שוון שוון



Nothing is overloaded, frame will not twist and stress suspension

Containers

- Containers provide:
 - Security (seal protection)
 - Weather Protection
 - Less damage to the cargo (if loaded properly)
 - Ease in handling
 - Concentration of unit supplies/equipment

AVAILABLE CONTAINERS

Requested through the ITO QUADCON






Coupling system

AVAILABLE CONTAINERS (Cont)

Requested through the ITO

TRICON





AVAILABLE CONTAINERS (Cont)








-MILVAN

20-Foot Shipping Container



40-Foot Shipping Container

ISU








ISU (Cont)

463L PALLET

ISU 90







Weapons Rack (300x M16, 60 x 9mm pistols)



Laundry Unit (4 washers/dryers)



Container Inspection - Inspect Containers Prior to Stuffing (exterior)

- Identification markings must be readable
- Welds must not be broken, cracked or missing
- Top/bottom rails should not be damaged
- Door frame must not be cut, broken, or distorted
- Locking bar guides must be serviceable
- Roof panels should not be corroded,

Container Inspection -

- Inspect Contain nterior to Stuffing (interior)
 - Ensure **no tears or holes** in sides and roof and
 - that floor boards are serviceable
 - Corner posts should not be dented, fractured, or torn
 - Ensure **no rust**, mold or mildew and check for
 - general cleanliness
- There may be an added cost for exchanging

Container Considerations

- Consider how you will receive


 container that is on a chassis, you will need a ramp or MHE for loading a container without a chassis, you will need MHE to place the container on a chassis or truck/trailer bed
- Considerating inspection requirements (inspect before the
- Container is loaded)
 Consider BBPCT requirements

Stuffing Containers

- Stuffing Containers
 - **Distribute** weight evenly over the container floor
 - Heavy cargo on bottom, lighter cargo on top
 - Fill space between cargo and containers sides with **blocking and bracing**
 - Keep CB as near as possible to the center
 - Do not overload the container

Load Placement in Containers

This placement secrens tire Wrong life & bends the trucks rearaxle housing; applying trailer brakes may lock the wheels & cause flat spots &



Wrong This placement overloads the trailer rear wheels so that brakes will not function properly & rubber scuffs away

Load Placement in Containers (Cont)



This container is loaded with the load spread low on the floor. (What is missing from picture?)


Record Weight

- Record weight & compare to the AUEL Verify the actual weight & dimensions of each piece of cargo, and vehicle with cargo
 - Cargo - Update AUEL if discrepancies are found
- You must <u>physically weigh</u> each vehicle after it is loaded

NEVER EXCEED VEHICLE'S CROSS
COUNTRY WEIGHT LIMITS

Lessons Learned

Tractor
 trailer that
 overloade
 d a bridge



SUMMARY

Planning the Load

- How to calculate the cubic feet required for cargo shipments, and how to determine if external cargo lift assets are required
- Vehicle weight limitations
- Testing the Load
 - Loading consideration for vehicles
 - Use of containers, including loading considerations





On Learnin

g

Question 1: What is the size in cubic feet of a packaged motor with the measurements of 48 in. wide, 24 in. high, and 72 in. long? Answer 1: 48 cubic feet.

 $(48 \times 24 [1152] \times 72 [82,944] / 1728 = 48 \text{ cuft})$



Question 2: When developing cargo load plans for vehicles, what is the vehicle weight category that you must not exceed?

Answer 2: You never exceed the vehicle's cross country weight.

Inspecting the Load

Preparing Vehicles For Shipment

- Thoroughly clean vehicles (customs)
- Ensure vehicles are mechanically sound (free of leaks, drips and other defects)
- Fill vehicle fuel tanks to a maximum of 3/4 full
- Do not fill the fuel tanks of trailer mounted equipment (such as generators) to more than 1/2 a tank
- Ensure tiedown/lifting devices are

convicable

58

Preparing Vehicles For Shipment (Cont)

- Shipment (Cont)
 Secure ignition keys to steering wheel with wire
- Ensure fire extinguishers are in approved brackets
- Do not lock driver compartments
- Consolidate radios and crew-served weapons in separate secured containers
- Basic Issue Items (jack, tools) stored in tool box (locked/banded)

Preparing Vehicles For Shipment (Cont)

Reduction

- Operational configuration for moving as convoy (reduction will occur in POE staging area if required)
- When vehicles are shipped
 - Reduce vehicle length and width by folding in side mounted mirrors
 - Remove antennas
 - Keep windshields and cab canvas in the 'up' position
 - Leave exhaust stacks in place
 - Reduce further only of specified in the

Movement Order

Securing Cargo in Vehicles and Containers

Packing Materials

- Types of packing materials:
 - Bubble wrap
 - Foam packing
 - Corrugated cardboard
 - Desiccant to dehumidify
 - Pneumatic & mechanical holding devices
- Materials also needed to close and secure boxes/cartons

Containers

- Rules for loading containers:

 Block & brace the cargo bottom,
 sides & front (stay 6 inches away from

 bedelite the weight evenly heavy
 items on the bottom of the container never overload
 - Package liquid on dunnage
 - Group cargo according to use at destination for ease of handling when off-loading

Containers (Cont)

SIX INCH GAP BEHIND DOOR

BLOCKING FOR EMPTY

USE DIVIDER SHEET BETWEEN

DIFFERENT SIZE / TYPE

SPACE ABOVE CARGO CARGO LIGHTER **CARGO ON TOP** D 0 0 HEAVY **CARGO** ON BOTTOM

BLOCKING & BRACING


DUNNAGE LAYERS OR PALLETS FOR POSSIBLE DRAINAGE

Blocking, Bracing, Packing, Crating, Tiedown (BBPCT)


- Units are responsible for securing their cargo
- Lashing should be:

1/2" manila rope, wire rope or banding material

- Secure rope to vehicle via hooks/rings on the vehicle's sides




Lashing



Blocking & Bracing

- Your unit is responsible for the blocking & bracing of unit equipment and containers
 - Use crib blocking whenever possible
 - Block cargo on all sides: front, back, sides & door area
 - Ensure there is no metal-to-metal contact (Use plywood, wood or cardboard)


Blocking & Bracing a 2-1/2 Ton Truck



MINIMIN - Denotes Blocking & Bracing

Blocking & Bracing a Container

False wall / side to side bracing



6" B & B at door | Blocking B & B between pallets

Loading Containers

- Once a container is blocked and braced:
 - Close and seal doors carefully (use serial numbered seals if provided)
 - Weigh the container and check its documentation
 - Place one copy of its packing list on the inside of the container door and one on the outside (in clear plastic sleeve for weatherproofing)
 - If carrying HAZMAT; load, label, and placard as appropriate

Cargo Protection

Protecting cargo from weather & elements is a <u>unit responsibility</u>

Place dunnage over corners to protect canvas

Cover open topped vehicles with canvas before lashing

Protect crew-served weapons from elements with a coating of grease

Inspecting the Load

- Once loading is completed, inspect the vehicle to ensure that:
 - Its overall dimensions (length, width and height) are in compliance with the applicable reduction policy Its overall weight is in compliance with stated vehicle limitations





Marking of Vehicles

Proper marking of unit vehicles and equipment:

FORSCOM/ARNG Reg 55-1, requires marking on front and back

Use 2" lettering placing UIC and SUN on bumpers

Suggested to mark all secondary loads that may be moved separately

See App G to FORSCOM/ARNG Reg 55-1

SUMMARY

- Inspecting the Load
 - Preparing vehicles for shipment
 - Securing cargo loads in vehicles and containers (lashing, and blocking and bracing)
 - Cargo protection (weatherproofing)
 - Vehicle weighing and marking

On Learnin



Question 1: What type of material should be used for lashing?

Answer 1: 1/2" manila rope, wire rope or banding material.



Question 2: How much space must be maintained between the cargo and the container door?

Answer 2: You must keep 6 inches of space between the cargo and the door.

Special Cargo Considerations

Types of Special Cargo

- Hazardous cargo (discussed in another lesson)
- Other Categories
 - Sensitive items
 - Classified material
 - Pilferable items

Sensitive Items



- Sensitive cargo is cargo that could <u>threaten</u>
 <u>public safety if compromised</u> (eg. weapons)
- Sensitive cargo must be secured and identified to port personnel so they can provide appropriate security
- Remove crew-served weapons from vehicles.
 Place them in containers that are sealed and secured with an approved locking device
- Provide guards or escorts when shipping sensitive material by rail

Ref: FM 4-01.011, Appendix D, pg

Sensitive Items (Cont)

Rules for sensitive cargo:

Packing material must be strong and durable enough to provide security protection in transit Containers, vehicles or compartments must be **secured** with appropriate locking device. Also place a serial-numbered seal on the door (serial number entered on unit packing list) Sensitive items must be **identified** in the commodity code of the unit's AUEL/DEL (OEL/UDL) The outside of container/vehicle/compartment must **NOT indicate** in any way that it contains sensitive items

Ref: FM 4-01.011, p.D-7

Classified Cargo

- Classified cargo is cargo that <u>requires protection in the</u> <u>interest of national security</u> (eg. codes)
- Classified material must be enclosed in two sealed containers: inner and outer container (comply with AR 380-5)
- Must NOT be identified as classified on the outer container
- Packing material must be strong and durable enough to provide security protection in transit, to keep items from breaking out of the container and to help detect any tampering with the container wrapping must conceal classified characteristics
- Not to be stored in any detachable storage
 compartment, such as vehicle trailers

Classified Cargo (Cont)

- When crossing international borders, arrangements must be made to ensure that customs, border or other inspectors (either US or foreign) do not open the classified material
- Containers, vehicles or compartments containing classified material must be secured with an appropriate locking device. Also place a serial-numbered seal on the door (serial number entered on packing list)
- Unit authorizing the transportation of classified equipment must notify their ITO/MCT and an appropriate carrier in advance
- Shipping classified material by rail may require the commander to provide guards or escorts
- When traveling by motor convoy, escorts must maintain constant surveillance of classified material (stay within escort's personal possession/observation at all times)

 Ref: FM 4-01.011, p.D-5

DD Form 1907

SIGNATURE AND TALLY RECO	ORD	Form Approved		DD Fo	1 C	007	
(See Dati 4500.9-R for guidence)		OMB No. 0702-0027	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	·)) C(少し) //	
(Use of equivalent carrier-furnished signature and tally a	record is acceptable.)	Expires Oct 31, 2001			<i></i>		
The public appoints bedon for this collection of information at estimated to everyon a min- patheting and institutions this data meeted, and completing and restlewing the collection of the public of the collection of the collection of the collection of the collection of Department of Deficiency (2020-0077), 121-5-101 restlements of the collection of th	ulse per responso. Including the time for no information. Bend comment reporting this into, Wathington facultarising Services, reporteding should be even the non-bendary play a currently valid OMB correct number. RETURN COMPLETED FORM AS	visiting instructions, soreming shalling users scarces, texton willmails or any inflar apper of this policition Directorals for information. Operations and Reports ending any other provision of law, no person shall be DIRECTED IN THE DISTRIBUTION.					
DISTRIBUTIO	N INSTRUCTIONS					1	
(1) The SHIPPER will print two copies, retain one copy and give on (2) The ORIGIN CARRIER will deliver one copy with original signatus). The DESTINATION CARRIER will attach and copy (reflecting all Transportation Charges, to the original Government Bill of Ladir OD Form 1907 will be delivered to the Consignee and one will (4) The CONSIGNEE will ensure Destination Carrier surrenders a re-	ures to the Osetination Carrier, I original signatures) and Stendard ng and torward for payment. Rep be retained.	roduced completed copy of) Est contacto	d lasds only) OR CONVEYANCE 15	5. FREIGHT CLASSIFICATION DE	13. NUMBER O	OF PIECES
	MPLETED BY THE SHIPPER	282004:191 12123		IBERS (For scaled sparts only)	E FREIGHT CEASSIFICATION DE	- SQRIP HIQIN	
1a. SHIPPER NAME	b. ORIGIN						
					700		
PROTECTIVE SERVICE REQUESTED 3. GBL OR CBL NUMBER		REQUIRING	LETED BY EACH PERSON ACCEPTING THE USE OF TRANSPORTATION P	G CUSTODY OF CLASSIFIED OR ROTECTIVE SERVICE DURING T	R PROTECTED MA RANSIT	TERIAL	
			AN A	**			
4a. CONSIGNEE NAME	b. DESTINATION	-	ON AND INTED	STATION INTERCHANGE POINT DESTINATION b.	SIGNATURE OF PERSON ACCEPTING CUSTODY	ACCEPTED 4.	PATE ACCEPTED (YYYYMMMOO)
5. PERMIT NUMBER (If any)	C The Michael Admin						
3. FERMIN NUMBER IN WAYY	6. TRANSPORTATION CONTI	KOL NUMBER		2000			
	10 00 000 0000000	99754					
7. ROUTING	8. WEIGHT	9. CUBE				100	
10. SPECIAL INSTRUCTIONS	100	11. DATE SHIPMENT TENDERED					
		TO CARRIER (YYYYMMOD)				-	
						1	
12. NAME OF CARRIER		13. NUMBER OF PIECES					
				+			
		'DD 10014 6					0.000
		DD FORM 1907, M	AY 2000	PREVIOUS EDITION	IS OBSOLETE.		

Pilferable Items

 Pilferable Items are items of value to individuals that can be readily removed and concealed (radios, binoculars compasses, etc.)

 Consider removing pilferable item from vehicles and packing them together in a separate container (also facilitates movement tracking)



Security

- Be prepared for acts of sabotage, espionage and terrorism in both CONUS and OCONUS theaters
- Guard against theft and pilferage
- Degree of security required will determine
 - the need for outside support
- References: FM 100-20, AR 380-

SUMMARY

Sensitive Items

Classified Cargo

Pilferable Items







g

Question 1: True or False: The contents of a classified cargo shipment must be clearly marked on the outer container or package during shipment?

Answer 1: False. Classified cargo must not be identified on the outer shipping container.

Documenting the Load

Forms Used

Forms

- FORSCOM Form 285-R, Vehicle Load Card
- DD Form 1750, Packing List
- DA Form 5748-R, Shipment Unit Packing List and Load Diagram
- DD Form 1387 Military Shipment Label
- Destination Placard
- Radio Frequency Identification Tags
- Shippers Declaration of Dangerous Goods
- DD Form 626, Motor Vehicle Inspection (Transporting Hazardous Materials)
- DD Form 836, Dangerous Goods Shipping Paper / Declaration and Emergency Response Information


Vehicle Load Card

FORSCOM Form 285-R

- Vehicle Load plans are documented on FORSCOM Form 285-R
 - FORSCOM Form 285-R must be filled out for all vehicles which have a cargo load
 - Load plans are kept on file as part of the unit movement plan and revised / tested annually


FORSCOM Form 285-R (Cont)

- Load cards can also be used to check cargo at terminals:
 - Check for loss or damage
 - Ensure particular cargo can be located when needed
- See example Form 285-R in FORSCOM/ARNG Reg 55-1, page 35



		Ve ni	C C C	<u> </u>	<mark>トᢏᢆ</mark>		
(TB 55-46-1 & 2) and (FORSCOM Reg 55-1)							
UNIT/UIC		V EH LIN NO	NOMEN/MOD NO	SBC/PLT A SGD	SHIPMENT UNIT NO	DATE COMPILED	
			IDTH OF VEH	HEGHT OF		V BH EMPTY WT	
OPERATIONAL REDUCED OPERATIONAL REDUCED OPERATIONAL REDUCED							
CARGO ARBA			CARGO ARBA CUBIC FT				
	NIGTH WIDTH HEIGHT OPERATIONAL REDUCED						
CB/OG IS	COMPUTE	N CHES FROM	TEST LOA	D V ERIFIED BY	5-R	DATE	
CB/CG IS NCHES FROM CARGO COM FORM 285-R							

Placetiffer Load Card here



Unit Name and UIC

Vehicle LiN and Index

Note in the Note in

Ref: FORSCOM/ARNG Reg 55-1, p.35No. of vehicle



Section / Platoon Shipment Unit No. (assigned by AUEL/OEL)

Date Compiled (YYYY/MM/DD

Ref: FORSCOM/ARNG Reg 55-1, p.35



Depending on the planned shipping configuration, either operational and/or reduced entries are made under length, width, and height of the vehicle.

Ref: FORSCOM/ARNG Reg 55.1, p.35

Jnder Bows Cargo Boay Lbading Height hot Cargo Deck Bed Heigh



Normally 'Under Bows Capacity'

Normally 'Top of Side Racks Capacity'

Dimensions and Weight of the cargo


area Ref: FORSCOM/ARNG Reg 55_™1, p.35



Center of balance / center of gravity (CB/CG) in inches

Point CB / CG calculated from (ref point) i.e. FFE = forward front edge

Ref: FORSCOM/ARNG Reg 55-1, p.35




Verified by (in pencil)

Date verified
(YYYY/MM/DD)
(in pencil)

Ref: FORSCOM/ARNG Reg 55,1, p.35

FORSCOM FORM 285-R Cargo Compartment



Cargo'

Location

Cargo compartment view Ref: FORSCOM/ARNG Reg 55-1, p.35

	Cargo	De	scrip	otion		
CARGO LOC NO	CARGO DESCRIPTION & TYPE PACK	NO OF ITEMS	PC CUBIC FT	TOTAL CUBIC FT	PC WT	TOTALWT
1	POL - 55 Gal Drum	3	6.8	20.4	380	1140

Cargo description for the three 55 gallon drums shown in the Cargo Compartment View section of the previous page

Ref: FORSCOM/ARNG Reg 55√1, p.35



Location number from drawing

Cargo descriptio n and type pack

Number of items in this location

Ref: FORSCOM/ARNG Reg 55-1, p.35



CuFt of each piece

Total CuFt Each
piece
weight
(pounds)

Total
weight of
this
location
(pounds)

Ref: FORSCOM/ARNG Reg 55-1, p.35



Location number from drawing

Number of items in this location

Total weight of this location

Ref: FORSCOM/ARNG Reg 55₇1, p.35

FORSCOM FORM 285-R

Cargo Description

TDA/MTOE PARA AND LIN NO OF DRIVER

16650

Para 109 Line 03

FORSCON Form 285-R, 1 Mar 93 EDITION OF 1 AUG 80 MAY BE USED. 5-1/23

Total weight of load plus empty vehicle weight (AC)


MTOE Paragraph and Line No. of Driver

Total weight of items loaded above the <u>red</u> <u>line</u> plus empty vehicle

Reserve Redline

 Redline concept is only used by the Reserve component

Total cargo moving from HS to MS



Cargo moving only from the HS to the MS (non-deployed equipment)

Ref: FORSCOM/ARNG Reg 5511, p.35

FORSCOM FORM 285-R

Reverse side of form, top

KEYELSE bt of BRPCT material

CARGOLOGINO	CARCO CESCRIPTION & TYPE PACK	NO CF ITTEMS	PCOUBICFT	TOTAL CUBICFT	PCWT	TOTALWIT		
I								
	VIBIGHT OF BEPOT MATTERIALS					<u> 168</u>		
	TCTALS+	8		622		3470		
NUMBERSOF D	D FORM 1750 (PACKING LIST) THIS LOAD =	5	***	V				

Total No. of DD Form 1750 (Packing Lists) for

Ref: FORSCOM/ARNG Reg 55-1, p.36

Totals (Items, cube & weight)

FORSCOM FORM 285-R

ROMERICA DE LA CONTRACTIONE RICHARDO RECORDE LA CONTRACTIONE RECORDE LA CONTRACTIONE RECORDE R

4 ea 4 X 4 X 12 80
12 ea 2 X 4 X 8 48
2 ea 5/8" Plywood 4 Ft X 8 Ft 40
168lbs

Remarks:

List BBPCT materials needed for cargo load - include weight

Ref: FORSCOM/ARNG Reg 55-1, p.36

DD Form 1750

Packing List


DD Form 1750 Packing List

DD Form 1750


Must be prepared for EACH multipack box or container

PACI	KING LIST	PACKED BY	1. NO. BOX	ES	2a REQUIS			
FACI	and List				2b. ORDER NO.			
B. END ITEM				-				
					5. PAGE OF		PAGES	
				Т	OLIANTITIES REQUIRED			
BOX NO.	CONTENTS	- STOCK NUMBER AND N (b)	OMENCLATURE	UNIT OF ISSUE (c)	INITIAL OPERATION (d)	RUNNING SPARES (e)	TOTAL	
(6)		147		10	19	(4)	19	
5. THIS CFRT	TIFIES THAT THE	TEMS LISTED HEREON AI	RE WITHIN THE SPECIFIE	D BOXES				
TYPED NAME	AND TITLE		SIGNATUR					

Ref: FORSCOM/ARNG Reg 55-1, p₄3₄7



Packed by: Enter your unit name and UIC Block 1: Number of inner boxes in the container (if Block 2a: relates to state that here the this to "Vehicle Bumper Number" or Block 2b: "Consmersian Container Berrham" AUEL/OEL or DEL/UDL for the vehicle/container



carrying the cargo (as shown) or the shipping container (eg.

'Box Shipping Metal 20ft. Serial #54280, HHC Seal Block 4: pate form compiled (YYYY/MM/DD) - Enter in

- Be specigencil Block 5: Page number - Enter page number & total number of pages

Ref: FORSCOM/ARNG Reg 55,1, p.37

Column (a): Box No.


BOX NO

ONTENTS - STOCK NUMBER AND NOMENCLATURE


Use when shipping 2 or more boxes in a container to indicate the box number in which the items are packed. If form is for a single box/crate leave blank

Ref: FORSCOM/ARNG Reg 55-1, p.37


Column (b): BOX NO Contents- Stock Number & Listritems with in the 1234-23-2334-4454 Chair, folding field box, crate or container. List the National Stock 1234-23-2451-6284 Number & Desk, field nomenclature/descripti on Indicate BBPCT materials **Wooden Crate** used and their weight at bottom Ref: FORSCOM/ARNG Reg 55-1, p₄3/7



Ref: FORSCOM/ARNG Reg 551, p.37




Ref: FORSCOM/ARNG Reg 55, p.37



Ref: FORSCOM/ARNG Reg 55,1, p.37

DOV. 110				ANTITIES REQU	IRED
BOX NO. (a)	CONTENTS - STOCK NUMBER AND NOMENCLATURE	UNIT OF ISSUE (c)	OPERATION	RUNNING SPARES	TOTAL
(a)	Must add statement: "This box (container) does (does not) contain hazardous material IAW 49 CFR "	(C)	Packs No in box	Weight of Each Item (Ibs)	Total Weight (lbs)



Block 6: Name and title (rormally primary or alternate UMO)

Block 7: Signature

Ref: FORSCOM/ARNG Reg 55.1, p.37

DA Form 5748-R

Shipment Unit Packing List and Load Diagram

DA Form 5748-R

- Can be used as a substitute for:
 FORSCOM Form 285-R or
 DD Form 1750
- Basically the combination of these two forms

DA Form 5748-R (Cont)

SHPMENT UNIT PACKINGLIST AND LOAD DIACRAM For use of this form; see RM55-65; the proponent agency is TRADOC				PAGE OF					
1 DEPLOYING UNIT		2 UICORBUMPERNO	2. UICOR BUMPERNO.		3. TON OR SEAL NUMBER				
4 SHPMBNT UNIT DESCRIPTION			5. DATE PACKED						
6. LENGTH	7. WIDTH	8. НВСНТ	8. HBGHT			12 LOCATION OF CG			
9. CUBE	10. BMPTYWBGHT	11 LOADEDWEIGHT							
13. PACKINGUST		_		+					
CARGO	CONTENTS		TYPE	PKG.	PKG.	TOTAL PKG.			
LOC, NO.	(Description and Noment lature)		PKG.	QTY.	WEIGHT.	WBGHT.			
а	Ь		С	d	e	f			

DA Form 5748-R (Cont)

		1			
14. CERTIFICATION. This certifies that items listed he			fied package:	3	
NOT TYPED NAME	b. GRADE	c. TITLE			
. SIGNATURE				e. DATE	
A FORM 5748-R, MAR 89					USAPPC V 1.

DA Form 5748-R (Cont)

SHPMENT UNIT PACKINGLIST AND LOAD DIAGRAM For use of this form; see RM55-65; the proponent agency is TRADOC				PAGE OF	
1 DEPLOYINGUNT A Co. 1-1	O IN WAB	2 UCOR BUMPER NO. A-4	1	3. TONOR SEAL NUMBER AWAF6A1\$0D	00010XX
4 SHPMENT UNIT DESCRIPTION		•	1	5. DATE PACKED	`
6. LENGTH	7. WIDTH	8. HBGHT		12. LOCATION OF CG	

Block 1: Deploying Unit (Designation and UIC)


Block 2: Bumper Number/Container

Identification Number

Block 3: TCN or Container Seal


Number

DA Form 5748-R (Cont)



Block 4: Shipment
Description
(model, nomenclature and
LIN/LIN Index)
Block 5: Date Packed
(YYYY/MM/DD)

Note: use this block for continuation pages



Cube


Block 10: Empty Weight

Block 12: Location of CG

Block 11: Loaded

130 Weight


DA Form 5748-R Blocks 13 relates to เคียง (Packing List)



DA Form 5748-R (Cont)

		T	I		
CARGO	CONTENTS	TYPE	PKG.	PKG.	TOTAL PKG.
LOC, NO.	(Description and Nomer clature)	PKG.	QTY.	WEIGHT.	WBGHT.
а	Ь	С	d	е	Ť
1	POL - 55 Gal Drum	Drum	3	38	114
	Column de				
	Column d:	COIL	ımn (e: cor	umn i
	Package	Pac	kage	Tot	al
		\			
	Quantity	VVe	ight	Pa	ckage
			•		
		(ea	<u>ch</u>	\/\ <i>\</i> c	ight
				1 7 7 C	IIUIIL
		•	7		_


DA Form 5748-R (Cont)



DA Form 5748-R (Cont)

Block 14: "Certification: This certifies that items listed herein are contained within the specified

Blocks a-c: 形色 / Grade / Title /




Block d: Signatur&lock e: Date (YYYY/MM/DD

DA Form 5748-R Reverse

15. LOAD DIAGRAM (Sketch cargo storage in space below)

Block 15:
Load Diagram
(Sketch cargo
storage
location)



DA Form 5748-R Reverse (Cont)

16. REMARKS

Tents are banded to warehouse pallet in two groups at location 2

Block 16:

Remark

S

REVERSE OF DA FORM 5748-R, MAR 89

- All vehicles (containing secondary cargo), containers, 468e 向即使民 must display a separate DD Form 1750/DA Form 5748-R (Packing List) showing its complete contents
- Items that are not transported in a container/crate - such as banded shovels, do not require a packing list. However, these items must be listed on the load diagram if they are loaded on a truck or in a container
- A packing list is not required for a container that already has a contents list - such as a toolbox
- Do not list classified material on packing lists

Documentation Requirements (Cont)

- Packing Lists (qty x 5) are distributed as follows:
 - 1. Filed in the unit movement plan
 - 2. Placed on the outside of the shipment unit where it is easily visible/accessible (placed inside a clear plastic sleeve for weatherproofing)
 - 3. Placed inside the shipment unit (includes sensitive item serial numbers)
 - 4. Prepared for the unit's representative (liaison team or supercargo)
 - 5. Retained by the hand receipt holder

Sensitive Items Packing List (Inside Container

	EDC/		QU	ANTITIES REQU	IR ED
BOX NO.	ensitive items listed individually	UNIT OF ISSUE (c)	OPERATION	RUNNING SPARES (e)	TO AL
	y serial number	y	Packs No in box	Weight of Each Item (lbs)	Total Weight (lbs)
1	NSN 8315-06-123-456 NVG ANPVS 7b Serial Numbers: B1234, B1235, B2345, B3456	EA	4	2	8
2	Paper, Toilet	вх	4	3	1 2
3	Fluid, Correction	BX	1	2	2

Never place this packing list on the outside of a container. The Sensitive Items Packing List is only placed on the inside of a container

Sensitive Items Packing List (Outside Container List)

	<u> </u>		QU	ANTITIES REQU	IR D
BOX N (a)	CONTENTS - STOCK NUMBER AND NOMENCLATURE (b)	UNIT OF ISSUE (c)	OPERATION	RUNNING SPARES (e)	TOTAL (f)
	Note: No sensitive items liste	d	Packs No in box	Weight of Each Item (lbs)	Total Weight (lbs)
1	Paper, Toilet	вх	4	3	1 2
2	Fluid, Correction	ВХ	1	2	2


Always place a DD form 1750 on the outside of your container that does not list the sensitive items

DD Form 1387

Military Shipment Label

DD Form 1387


Military
Shipment
Label





MSL Guidelines


- Weigh and measure the dimensions of vehicles/containers and update DEL/UDL prior to printing MSLs - information shown on the MSLs must be accurate
- Ensure MSLs can be easily found (so that they can be scanned at transit locations)
- Do not mark the barcode for any reason it will make it unreadable (if the label must be physically marked to show it has been scanned - mark somewhere other than the barcode)
- If the load of a vehicle/container is changed a new MSL must be produced
- When attaching MSLs, ensure the surface area where the label will be attached is clean and dry - this allows the adhesive on the label to stick
- Remove MSLs once the deployment is complete

MSL Placement -










MSL Placement -

Paide MSLs on one end and on the adjacent and for and for

containers, attach MSLs to the right side door and to the right side of the container as you look



DESTINATION PLACARD

int on 8.5 imes 11 inch paper and place in a clear sealed plastic

Unit: 118th INF BN, 2nd BDE, 1ID

UIC: WTA377
ULN: CDAAP30


Destination: Kosovo (Camp


Bondsteel)

Unit: A Co., 1-36 INF BN, 1st BDE, 1AD

UIC: WAE3A0 ULN: EDAAP15

Destination: Kuwait (Camp Doha)







BDE, 1AD

UIC: WAE3A0
ULN: EDAAC15


Destination: Kuwait (Camp



- Radio Frequency Tags

 If Radio Frequency Identification (RFID) tags are being used the required information must be the red before departing your home station
- RFID Tags are mounted (using two long nylon strips more durable than plastic straps) as follows:
 - Vehicles: Attached to the top of the radiator grill (wheeled vehicles)/front of the vehicle (tracked vehicles)
 - Containers: Attached to the locking bar located on the door near the upper right-hand corner - you may also use zip ties to attach the RFID tag to containers (do not drills holes in containers to mount the tags)
 - 463L Pallets: Placed adjacent to the MSL
- Tie down both the top and the bottom of the tag so that it will not bounce and be damaged during shipment
- Note that the data on the RFID tag must be updated if the


RFID Tag Placement













Shipping Documents Stowage Location

Wheeled Vehicles:
Seal all documents in a clear zip-lock plastic bag and place inside the vehicle on the passenger side's windscreen.

Tracked Vehicles: Seal all documents in a clear zip-lock plastic bag and tape to the outside front driver's side



Containers: Seal all documents in a clear zip-lock plastic bag and tape to the outside of the door.



Summary

• Forms:

- FORSCOM Form 285-R, Vehicle Load Card
- DD Form 1750, Packing List
- DA Form 5748-R, Shipment Unit Packing List and Load Diagram
- DD Form 1387 Military Shipment Label
- Destination Placard
- Radio Frequency Identification Tags
- Shippers Declaration of Dangerous Goods
- DD Form 626, Motor Vehicle Inspection (Transporting Hazardous Materials)
- DD Form 836, Dangerous Goods Shipping Paper / Declaration and Emergency Response Information





Question 1: Where can you find guidance on filling out FORSCOM Form 285-R?

Answer 1: FORSCOM/ARNG Regulation 55-1.



Question 2: What is the purpose of DD Form 1750?

Answer 2: The DD Form 1750 is used to document the contents of packages, boxes, pallets or any other container that consists of multiple cargo items.



Question 3: DA Form 5748-R can be used as an authorized substitute for what other forms?

Answer 3: FORSCOM Form 285-R and DD Form 1750



Question 4: Load cards are not just used to document loads. What else can they be used for?

Answer 4: They are also used to check for lost or damaged cargo at terminals or to find a particular piece of cargo.







On Review

Question 1: What should you check to ensure that secondary loads in the back of a unit vehicle are correctly prepared for movement? Answer 1: Make sure the items are properly loaded, blocked and braced, protected from the elements and properly lashed to the vehicle.



On Review

Question 2: Where can you find the axle weight capacity of a vehicle?

Answer 2: The vehicle data plate lists each axle weight carrying capacity.



Question 3: What is the most important aspect of shipping classified material?

Answer 3: You must <u>never</u> indicate that there is classified material on the outside of a package or shipping container



Question 4: What form can be used as both a vehicle load form and a packing list form?

Answer 4: DA Form 5748-R, Shipment Unit Packing List and Load Diagram.

QUESTIONS

